

# SAVOX

## SAVOX C-C440/Sailor Ex Com control unit

The SAVOX C-C440 com-control unit is a push-to-talk unit designed for use with your two-way radio in demanding environments. It offers easy and reliable communication for professionals requiring durable equipment when operating in harsh conditions, and is ideal for those who need to communicate hands-free and/or with their radio secured underneath protective clothing. With a headset it provides a hands-free way to stay connected with your team and ensure the efficiency and safety of your operations. Rugged to IP67 and available as an ATEX version. Ex variants can be recognized by their different PTT button color (dark blue).



### Key benefits

- Dust proof and water submersible (IP67)
- Extra large push-to-talk button
- Excellent tactile feel and operation; suitable for wearing under clothing and with gloves
- Large 360° rotating clip

|                                      |   |
|--------------------------------------|---|
| Market Segment                       | Public Safety   |
| Size L                               | 89.8 mm   |
| Size H                               | 87.9 mm   |
| Weight (text)                        | 140 g   |
| Operational Temperature Max          | 85 °C (185 °F)  |
| Storage Temperature Min              | -25 °C (-13 °F)   |
| Protection Against Drop(fall)        | 1 meter, IEC 60068-2-31-2008  |
| Battery Life Time                    | No battery  |
| Cable Type                           | Coiled  |
| Electro Magnetic Compatibility (EMC) | EN  |
| Emergency Button                     | No  |
| Price List Notes                     | EX II 2 G, Ex ib IIC T4 Gb, EX II 2 D, Ex IIIC T110 Db, ATEX and IECEx approved Sold only through Thrane & Thrane |

|                             |   |
|-----------------------------|---|
| Product code                | L443922                                   |
| Size W                      | 30.9 mm                                   |
| Housing Colour              | Black                                     |
| Operational Temperature Min | -40 °C (-40 °F)                           |
| Ingress Protection          | IP66, IP67                                |
| Storage Temperature Max     | 70 °C (158 °F)                            |
| Headset Connector           | QR4+1 female                              |
| Connectivity                | Wired                                     |
| Use Voltage                 | 3.0...10VDC (0VDC for dynamic microphone) |
| Ex/IS                       | ATEX / IECEx                              |
| Attachment/Fastening        | Clothing Clip                             |

**Tecnitrán**  
TELECOMUNICACIONES

Madrid: 916 106 678 | Valencia: 960 699 593 | Mallorca: 871 620 033

www.tecnitrán.es | info@tecnitrán.es

Síguenos en:    